

## BCS M12B4G2-PSC40D-S04K

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Balluff                          |
| <b>Catalog number</b> | bcs-m12b4g2-psc40d-s04k          |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

### Technical specification

|  |                        |
|--|------------------------|
| <b>Installation (CAL)</b>                    | for flush mounting     |
| <b>Connection Type #1</b>                    | Connector              |
| <b>Housing Material (PM)</b>                 | 1.4305 stainless steel |
| <b>Min Range (PM)</b>                        | 1 mm                   |
| <b>Max Range (PM)</b>                        | 4 mm                   |
| <b>SAP EAN11</b>                             | BCS00P0                |
| <b>Interface Key</b>                         | PNP normally open (NO) |
| <b>Protection Type (IEC 60529)<br/>[BAS]</b> | IP67                   |
| <b>Dimension</b>                             | Ø 12 x 75 mm           |
| <b>Approval Conformity</b>                   | CE, UKCA, cULus, WEEE  |
| <b>Operating Voltage (UB)</b>                | 10...30 VDC            |
| <b>Weight</b>                                | 0.01 kgs               |