

## BES 516-113-SA3-S4-C

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Balluff                          |
| <b>Catalog number</b> | bes-516-113-sa3-s4-c             |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

### Technical specification

|   |                       |
|---|-----------------------|
| <b>Switching Output</b>                 | PNP                   |
| <b>Max Range SN</b>                     | 1.5 mm                |
| <b>Protection Type (IEC 60529) [PM]</b> | IP68                  |
| <b>Connection Type #1</b>               | Connector             |
| <b>Max Ambient Temperature (PM)</b>     | 85 °C                 |
| <b>Switching Function</b>               | NO/NC                 |
| <b>Style</b>                            | M12x1                 |
| <b>Installation (PM)</b>                | for flush mounting    |
| <b>Length (PM)</b>                      | 70 mm                 |
| <b>SAP EAN11</b>                        | BES032M               |
| <b>Housing Material (PM)</b>            | Stainless steel       |
| <b>Approval Conformity</b>              | CE, UKCA, cULus, WEEE |
| <b>Weight</b>                           | 0.45 kgs              |