

## BES M08MM-PSC40B-BP00,3-GS49

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Balluff                          |
| <b>Catalog number</b> | bes-m08mm-psc40b-bp003-gs49      |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

### Technical specification

|   |                       |
|---|-----------------------|
| <b>Switching Function</b>               | normally open (NO)    |
| <b>Housing Material (PM)</b>            | Brass                 |
| <b>Length (PM)</b>                      | 60 mm                 |
| <b>Connection Type #1</b>               | Cable with connector  |
| <b>Max Range SN</b>                     | 4 mm                  |
| <b>Approval Conformity</b>              | CE, UKCA, cULus, WEEE |
| <b>Max Ambient Temperature (PM)</b>     | 70 °C                 |
| <b>Style</b>                            | M8x1                  |
| <b>Switching Output</b>                 | PNP                   |
| <b>SAP EAN11</b>                        | BES05U8               |
| <b>Protection Type (IEC 60529) [PM]</b> | IP67                  |
| <b>Installation (PM)</b>                | quasi-flush           |