CP2916-0000

Industrial automation components

Add to quote

Ask about this product



Manufacturer	Beckhoff
Catalog number	cp2916-0000
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Display Size	15.6 inches
Display Resolution	1366 x 768 pixels
Housing Material	Aluminum with glass front
Operating Temperature	0 to 55 °C
Front Protection Rating	IP65
Rear Protection Rating	IP20
Connection Technology	DVI-E and USB-E
Max Distance PC to Control Panel	50 meters
USB Ports	2 x USB 3.0
Power Supply	24 V DC
Touch Input	Multi-finger touch screen

Description

The Beckhoff CP2916-0000 is a 15.6-inch multi-touch built-in control panel designed for industrial applications. It features a 1366 x 768 resolution display, housed in an aluminum enclosure with a glass front, ensuring durability and a sleek design.

The panel operates within a temperature range of 0 to 55°C and offers front-side protection rated at IP65 and rear-side protection at IP20, making it suitable for various industrial environments. Connectivity options include DVI-E and USB-E interfaces, allowing the control panel to be connected to a PC at distances up to 50 meters.

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE
VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.

Additionally, it provides two USB 3.0 ports for direct connections. The CP2916-0000 is powered by a 24 V DC supply and supports multi-finger touch input, enhancing user interaction. This control panel is ideal for applications requiring robust and reliable human-machine interfaces in industrial settings.

AUTOMATION TRADER

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE

VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.