

## M105RGB14

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Control Techniques               |
| <b>Catalog number</b> | m105rgb14                        |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

### Technical specification

|                             |             |
|-----------------------------|-------------|
| <b>Voltage</b>              | 220 - 480 V |
| <b>Cooling Capacity</b>     | 37.5 kW     |
| <b>Signal Type</b>          | 480         |
| <b>Signal Level</b>         | 480 V       |
| <b>Relay Specifications</b> | 480 VAC     |
| <b>Current</b>              | 88 A        |
| <b>Power</b>                | 37.5 kW     |
| <b>Frequency</b>            | 50 - 60 Hz  |
| <b>Horsepower</b>           | 37.5 KW     |
| <b>Product Type</b>         | Drive       |

### Description

The M105RGB14 is an advanced drive from CONTROL TECHNIQUES, designed to operate within a voltage range of 220 to 480 V. It offers a current of 88 A and a power output of 37.5 kW, making it an ideal solution for demanding applications. The device operates at a frequency of 50-60 Hz, ensuring high cooling efficiency and precise signal control at a level of 480. The relay specification also stands at 480, ensuring reliability and stability in operation.