HG-H354BS-D48

Industrial automation components

Add to quote

Ask about this product



Manufacturer	Mitsubishi
Catalog number	hg-h354bs-d48
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Product Type	AC Brushless Servo Motor
Rated Output	3.5 kW
Rated Speed	3,000 rpm
Rated Torque	11.1 N·m
Flange Size	176 mm square
Flange Fitting Diameter	114.3 mm
Shaft Diameter	35 mm
Protection Rating	IP67
Encoder Resolution	1,048,576 pulses per revolution pulses/rev
Compatible Drive Units	MDS-EJ-SP2-80, MDS-EJ-SP2-160

Description

HG-H354BS-D48 - AC brushless servo motor, HG Series, Mitsubishi. Rated output 3.5 kW, rated speed 3,000 rpm, rated torque 11.1 N·m. Straight shaft, built-in absolute position encoder with 1,048,576 pulses per revolution.

Flange: 176 mm square; flange fitting diameter 114.3 mm; shaft diameter 35 mm. Protection: IP67. Compatible with MDS-EJ-SP2-80 and MDS-EJ-SP2-160 drive units.

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE
VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.