

## MDS-C1-V2-4520

Industrial automation components

<b>Manufacturer</b>	Mitsubishi
<b>Catalog number</b>	mds-c1-v2-4520
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

### Technical specification

<b>Weight</b>	4.99 kgs kg
<b>Product Type</b>	2-Axis AC Servo Drive Unit
<b>Rated Output Power</b>	6.5 kW
<b>Output Voltage</b>	155 V AC
<b>Rated Output Current (Axis 1)</b>	28.0 A
<b>Rated Output Current (Axis 2)</b>	16.0 A
<b>Input Voltage Range</b>	270 to 311 V AC
<b>Input Current</b>	44 A
<b>Control Power Voltage</b>	200 to 230 V AC
<b>Control Power Frequency</b>	50 or 60 Hz
<b>Protection Rating</b>	IP20
<b>Braking Type</b>	Regenerative and Dynamic Brakes
<b>External Analog Output</b>	0 to +5 V, 2 channels

### Description

The MDS-C1-V2-4520 is an industrial product weighing 4.99 kg, making it suitable for applications requiring mobility and easy installation. Its design ensures durability and reliability in challenging working conditions.