

## MR-J2S-100A-S055

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Mitsubishi                       |
| <b>Catalog number</b> | mr-j2s-100a-s055                 |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

### Technical specification

|                             |             |
|-----------------------------|-------------|
| <b>Frequency</b>            | 50 - 60     |
| <b>Horsepower</b>           | 1           |
| <b>Measurement Range</b>    | 200 - 230   |
| <b>Signal Level</b>         | 230 V       |
| <b>Relay Specifications</b> | 100 A       |
| <b>Voltage</b>              | 200 - 230 V |
| <b>Current</b>              | 5 A         |
| <b>Power</b>                | 1           |
| <b>Cooling Capacity</b>     | 1           |
| <b>Product Type</b>         | Drive       |
| <b>Manufacturer</b>         | Mitsubishi  |

### Description

The MR-J2S-100A-S055 drive from Mitsubishi is an advanced solution operating within a voltage range of 200-230 V and a current of 5 A. It provides a power output of 1 kW and operates at a frequency of 50 to 60 Hz. Both the cooling efficiency and motor power are rated at 1 kW, making it ideal for applications requiring precise control. The signal level is 230, and the relay specification is 100.