

## NF125-CV 3P 80A

Industrial automation components

<b>Manufacturer</b>	Mitsubishi
<b>Catalog number</b>	nf125-cv-3p-80a
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Legacy / discontinued

### Technical specification

<b>Weight</b>	0.45 kgs
<b>Material Number</b>	254812
<b>Business Area Code</b>	FK
<b>Product Category</b>	LVS
<b>Pricing Group</b>	FK - LVS
<b>Product Name</b>	NF125-CV 3P 80A
<b>Marketing Note [PL]</b>	57.34
<b>Class Code</b>	100100901
<b>Class Description</b>	FA-MCCB: Moulded-Case Circuit Breaker
<b>Sub Product Line</b>	MCCB
<b>Product Hierarchy Code</b>	IAN10201
<b>Product Line</b>	WS-V 1 - NF Body
<b>Gross Weight (kg)</b>	0.816
<b>Gross Length (cm)</b>	14
<b>Gross Width (cm)</b>	10
<b>Gross Height (cm)</b>	10
<b>Customs Tariff Code</b>	85362010
<b>Country of Origin</b>	JP
<b>ABC Classification</b>	B
<b>Product Marketing Description</b>	Circuit breaker 3pole. In = 80A; Icu / Ics = 10 / 5kA at AC 440V

## Description

LVS | MCCB | Circuit breaker 3pole. In = 80A; Icu / Ics = 10 / 5kA at AC 440V