

## NF400-SEW 3P 400A

Industrial automation components

<b>Manufacturer</b>	Mitsubishi
<b>Catalog number</b>	nf400-sew-3p-400a
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Legacy / discontinued

### Technical specification

<b>Weight</b>	6.15 kgs
<b>Material Number</b>	204780
<b>Business Area Code</b>	FK
<b>Product Category</b>	LVS
<b>Pricing Group</b>	FK - LVS
<b>Product Name</b>	NF400-SEW 3P 400A
<b>Marketing Note [PL]</b>	334.17
<b>Class Code</b>	100100901
<b>Class Description</b>	FA-MCCB: Moulded-Case Circuit Breaker
<b>Sub Product Line</b>	MCCB
<b>Product Hierarchy Code</b>	IAN10123
<b>Product Line</b>	WSS 2 - NF Body
<b>Gross Weight (kg)</b>	6.85
<b>Gross Length (cm)</b>	22
<b>Gross Width (cm)</b>	40
<b>Gross Height (cm)</b>	20
<b>Customs Tariff Code</b>	85362090
<b>Country of Origin</b>	JP
<b>ABC Classification</b>	A
<b>Product Marketing Description</b>	Circuit breaker 3pole. Ir = 200 - 400A; Icu = Ics = 42kA at AC 440V

## Description

LVS | MCCB | Circuit breaker 3pole. Ir = 200 - 400A; Icu = Ics = 42kA at AC 440V