NZ2GF2B1-32T

Industrial automation components

Add to quote

Ask about this product



Manufacturer	Mitsubishi
Catalog number	nz2gf2b1-32t
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Output Type	Transistor Output (Sink Type)
Output Points	32 points
Rated Load Voltage	12/24 V DC
Maximum Load Current	0.5 A per point, 5 A per common terminal
Response Time	1.5 ms
Wiring Type	1-wire terminal block
Compliance Standards	UL, cUL, CE (EMC), CE (RoHS), KC (EMC), LR, NK, DNV, ABS, RINA, BV

Description

NZ2GF2B1-32T - transistor output module, Mitsubishi. 32 output points in sink type configuration; rated load voltage 12/24 V DC. Maximum load current is 0.5 A per point and 5 A per common terminal.

Response time: 1.5 ms. Wiring: 1-wire terminal block. Standards: UL, cUL, CE, KC, LR, NK, DNV, ABS, RINA, BV.

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE
VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.