

## E3AS-HL500MT-M3J 0.3M

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Omron                            |
| <b>Catalog number</b> | e3as-hl500mt-m3j-03m             |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

### Technical specification

|                               |  |
|-------------------------------|--|
| <b>Display Name</b>           | E3AS-HL500MT-M3J 0.3M  |
| <b>Description</b>            | Photoelectric sensor, rectangular housing, stainless steel, red laser class 1, background suppression, spot beam, 35-500 mm, 10-30 VDC, PNP, Light-ON/Dark-ON, IO-Link COM3, M8 pigtail connector 4-pin, 0.3 m |
| <b>ETIM Class</b>             | EC002719   |
| <b>EAN</b>                    | 4549734663601.0  |
| <b>Group</b>                  | GD   |
| <b>Fam</b>                    | GDH  |
| <b>Country of Origin</b>      | CHN  |
| <b>Tariff Code</b>            | 8541490000.0   |
| <b>OC Code</b>                | E3AS0123M  |
| <b>Second Item Number</b>     | E3ASHL500MTM3J03MOMS   |
| <b>Category</b>               | Czujniki fotoelektryczne E3AS  |
| <b>Stat Fam</b>               | BAAA   |
| <b>Stat Fam description</b>   | E3AS   |
| <b>Publication sort</b>       | 4AAA1  |
| <b>Primary Package Length</b> | 121  |
| <b>Primary Package Width</b>  | 125  |
| <b>Primary Package Depth</b>  | 88   |
| <b>Dimensions</b>             | 121mm x 125mm x 88mm   |
| <b>Primary Package Weight</b> | 190.5 g  |