

## E3FA-RP22

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Omron                            |
| <b>Catalog number</b> | e3fa-rp22                        |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

### Technical specification

|                               |                                                                                                                                     |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| <b>Display Name</b>           | E3FA-RP22                                                                                                                           |
| <b>Description</b>            | Photoelectric sensor, M18 threaded barrel, plastic, red LED, coaxial retro-reflective, 500 mm, PNP, Light-ON/Dark-ON, M12 connector |
| <b>ETIM Class</b>             | EC002717                                                                                                                            |
| <b>EAN</b>                    | 4548583440883.0                                                                                                                     |
| <b>Group</b>                  | GD                                                                                                                                  |
| <b>Fam</b>                    | GDS                                                                                                                                 |
| <b>Country of Origin</b>      | IDN                                                                                                                                 |
| <b>Tariff Code</b>            | 8536909500.0                                                                                                                        |
| <b>OC Code</b>                | E3FA2035A                                                                                                                           |
| <b>Second Item Number</b>     | E3FARP220MI                                                                                                                         |
| <b>Category</b>               | Czujnik optyczny E3FA/E3                                                                                                            |
| <b>Stat Fam</b>               | BAAD                                                                                                                                |
| <b>Stat Fam description</b>   | E3F_ & E3R_                                                                                                                         |
| <b>Publication sort</b>       | 4ACA1                                                                                                                               |
| <b>Primary Package Length</b> | 1                                                                                                                                   |
| <b>Primary Package Width</b>  | 1                                                                                                                                   |
| <b>Primary Package Depth</b>  | 1                                                                                                                                   |
| <b>Dimensions</b>             | 1mm x 1mm x 1mm                                                                                                                     |
| <b>Primary Package Weight</b> | 27 g                                                                                                                                |

## Description

Photoelectric sensor, M18 axial, plastic body, red LED, coaxial retro-reflective, 0-500m, PNP, L-ON/D-ON selectable, M12 connector