

## SHL-W255

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Omron                            |
| <b>Catalog number</b> | shl-w255                         |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

### Technical specification

|                               |  |
|-------------------------------|--|
| <b>Display Name</b>           | SHL-W255   |
| <b>Description</b>            | Enclosed switch, short hinge roller lever, SPDT, 10A |
| <b>ETIM Class</b>             | EC000030   |
| <b>EAN</b>                    | 4536853781408.0                                      |
| <b>Lot Qty</b>                | 10   |
| <b>Group</b>                  | CG   |
| <b>Fam</b>                    | CGI  |
| <b>Country of Origin</b>      | JPN  |
| <b>Customs Tariff Code</b>    | 8536501590.0   |
| <b>OC Code</b>                | SHLN2800F  |
| <b>Second Item Number</b>     | SHLW255  |
| <b>Category</b>               | Wyłącznik Krańcowy - SHL                             |
| <b>Stat Fam</b>               | MABG   |
| <b>Stat Fam description</b>   | SHL  |
| <b>Publication sort</b>       | 4GAF1  |
| <b>Primary Package Length</b> | 76   |
| <b>Primary Package Width</b>  | 39   |
| <b>Primary Package Depth</b>  | 22   |
| <b>Dimensions</b>             | 76mm x 39mm x 22mm                                   |
| <b>Primary Package Weight</b> | 68 g   |

## Description

SHL-W255 | Omron, Enclosed Limit Switch, Roller Lever Mechanism, IP67, 125 V ac | Brand / Manufacturer: Omron | product type: Enclosed Limit Switch | operating mechanism: Roller Lever | level of security: IP67 | minimum operating voltage: 125 V ac;8 V dc | maximum operating voltage: 250 V ac/dc | minimum process temperature: -10 °C | maximum working temperature of the process: +80 °C | requirements met: UL Listed;CSA Certified;CCC Approved;cULus Listed;CE Certified | length: 73.5 mm