NBB20-L2-E2-V1

Industrial automation components

Add to quote

Ask about this product



Manufacturer	Pepperl+Fuchs
Catalog number	nbb20-l2-e2-v1
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.14 kgs
Connection Elements / Additional Info	M12x1 plug-in receptacle / DC sensors
Electrical Output	3-wire / DC / PNP / N.O.
Sensing Range	20mm sensing range
Series	L2 Series
Napięcie zasilania	10 - 30 V
Measurement Range	10 - 30
Product Type	Sensor
Signal Type	30
Signal Level	30 V
Manufacturer	Pepperl+fuchs
Zasięg wykrywania	20 mm
Typ wyjścia	PNP-NO
Napięcie zasilania	10-30 V DC
Częstotliwość przełączania	0-440 Hz
Stopień ochrony	IP69K
Typ złącza	M12 4-pin

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE
VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.

Zakres temperatury pracy	-25 do +85 °C
Wska□nik LED	4-way

Description

NBB20-L2-E2-V1 | Pepperl + Fuchs, NBB20 Series, Inductive Sensor, Block, M12 x 1, 20 mm, 1NO/PNP, 10 to 30 V dc, 0 to 200 mA, 0 to 440 Hz, PA, 12 mm, 40 mm, 67 mm, 40 mm | Brand / Manufacturer: Pepperl + Fuchs | product type: Inductive Sensor | series: NBB20 | body style: Block | thread size: M12 x 1 | detection area: 20 mm | output function: 1NO;PNP | rated voltage: 10 to 30 V dc | current rating: 0 to 200 mA | maximum switching frequency: 0 to 440 Hz | housing material: PA | diameter: 12 mm | minimum operating temperature: -25 °C | maximum working temperature: +85 °C | length: 40 mm | width: 67 mm | height: 40 mm