VMT-5015-SM-DE

Industrial automation components

Add to quote

Ask about this product



Manufacturer	Phoenix Contact
Catalog number	vmt-5015-sm-de
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Processor	Intel® Celeron® M ULV 800 MHz
RAM	1 GB DDR
Storage	2.5" HDD, min. 40 GB, 24x7 Automotive
Display	15" TFT, 1024 x 768 pixels
Touchscreen	Resistive industrial touchscreen
Interfaces	COM 1 (RS-232), PS/2 mouse, PS/2 keyboard, 2x USB, Line Out, Ethernet (10/100 Mbps)
Protection Class	IP65
Operating Temperature	-20°C to 45°C
Humidity Range	10% to 85% (non-condensing)
Mounting Options	Support brackets, table stands, VESA standard brackets, Rittal bracket connection adapters

Description

The Phoenix Contact VMT 5015 SM DE is a high-performance industrial panel PC designed for demanding applications requiring robust computing capabilities in challenging environments. Featuring a 15-inch color TFT display with a resolution of 1024 x 768 pixels, it offers clear and precise visuals.

The resistive industrial touchscreen ensures reliable input even in harsh conditions. Encased in a durable aluminum die-cast housing, the device boasts an IP65 protection rating, making it resistant to dust and water ingress.

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE
VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.

This rugged design is ideal for mobile applications, with a wide operating voltage range of 19 to 29 V DC. The VMT 5015 SM DE is equipped with an Intel® Celeron® M ULV 800 MHz processor, 1 GB DDR RAM, and a 2.5".

AUTOMATION TRADER

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE

VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.