ATS48D88YS316

Industrial automation components

Add to quote

Ask about this product



Manufacturer	Schneider Electric
Catalog number	ats48d88ys316
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Product Type	Soft Starter
Product Family	Altistart 48
Voltage Range	208 to 690 V
Current Rating	77 A
Horsepower	Up to 75 kW
Dimensions	190 x 290 x 235 mm
Weight	8.3 kg
Compliance	IEC 60947-4-2
Certifications	DNV, UL, CCC, CSA, GOST, C-Tick, SEPRO, TCF, NOM 117

Description

The Schneider Electric ATS48D88YS316 is a soft starter designed for asynchronous motors, particularly suitable for heavy-duty industrial applications and pumps. Part of the Altistart 48 series, this device offers a rated current of 77 A and operates within a voltage range of 208 to 690 V, accommodating both standard and severe applications. It supports motor power up to 75 kW, with specific ratings depending on the voltage and application severity. The ATS48D88YS316 features a compact design with dimensions of 190 x 290 x 235 mm and weighs 8.3 kg, facilitating easy integration into various industrial setups. It complies with IEC 60947-4-2 standards and holds certifications including DNV, UL, CCC, CSA, GOST, C-Tick, SEPRO, TCF, and NOM 117, ensuring reliability and safety in diverse operational environments.

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE
VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.