

## ATV31HU40M3XA

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Schneider Electric               |
| <b>Catalog number</b> | atv31hu40m3xa                    |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

### Technical specification

|                             |            |
|-----------------------------|------------|
| <b>Voltage</b>              | 208 V      |
| <b>Power</b>                | 4          |
| <b>Horsepower</b>           | 4          |
| <b>Frequency</b>            | 50 - 60 Hz |
| <b>Cooling Capacity</b>     | 4          |
| <b>Product Type</b>         | Drive      |
| <b>Signal Type</b>          | 208        |
| <b>Signal Level</b>         | 208 V      |
| <b>Relay Specifications</b> | 208 VAC    |

### Description

The ATV31HU40M3XA is a drive from Schneider Electric, designed to operate at a voltage of 208V. It offers a power rating of 4 kW and operates within a frequency range of 50 to 60 Hz. This drive supports motors with a power of 4 kW, providing a cooling efficiency of 4 kW. Both the signal type and signal level are 208, making it suitable for various industrial applications.