

### 1FK2102-1AG00-1SA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	1fk2102-1ag00-1sa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>EAN</b>	4042948690468.0
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Configurable Product</b>	True
<b>Customs Tariff Code</b>	85015100
<b>Copper Weight</b>	0
<b>UPC</b>	804766728105.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	9021
<b>Weight</b>	600
<b>Product ID</b>	1FK2102-1AG00-1SA0
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.07.2006
<b>Country of Origin</b>	R0
<b>eClass 6</b>	27-02-26-02
<b>eClass 7.1</b>	27-02-26-02
<b>eClass 8</b>	27-02-26-02
<b>eClass Version 9</b>	27-02-26-02
<b>eClass Version 9.1</b>	27-02-26-02
<b>ETIM 7</b>	EC001851
<b>Group Classification Key</b>	R220
<b>List of Characteristics</b>	D32
<b>Metals Coefficient</b>	-----71
<b>Packaging Width</b>	250,00
<b>Packaging Height</b>	267,00
<b>Comparative Metals Coefficient</b>	01.07.2006
<b>Unit of Measure</b>	ST
<b>Product Description</b>	SIMOTICS S-1FK2 HD servo motor M0=0.32 Nm; PN = 0.1 kW at nN=3000 rpm (200-240 V); degree of protection IP64; shaft D8x25mm with fitted key; absolute encoder single-turn 22-bit (encoder AS22DQC); with OCC interface; plug size M12, rotatable
<b>AL Field</b>	N
<b>ECCN</b>	N
<b>Packaging Length</b>	452,00
<b>Packaging Size</b>	MM