

1FK2306-4AC00-0MB0

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 1fk2306-4ac00-0mb0 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|---------------------------------------|--|
| Product Description | SIMOTICS S-1FK2 HI servo motor M0=12 Nm; PN = 2.2 kW at NN=2000 rpm, (380-480 V); degree of protection IP64; cylindrical shaft D24x50 mm; absolute encoder 22-bit + 12-bit multiturn (encoder AM22DQC); with DRIVE-CLiQ plug M17; power connector size M23 |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85015220 |
| Copper Weight | 0 |
| EAN | 4025515669890.0 |
| Quantity in Package | 1 |
| UPC | 195125107342.0 |
| Weight | 11400 |
| Product ID | 1FK2306-4AC00-0MB0 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 01.06.2019 |
| Configurable Product | False |
| Country of Origin | CN |
| ECCN | N |
| eClass 6 | 27-02-26-02 |
| eClass 7.1 | 27-02-26-02 |
| eClass 8 | 27-02-26-02 |
| eClass Version 9 | 27-02-26-02 |
| eClass Version 9.1 | 27-02-26-02 |
| ETIM 7 | EC001851 |
| Group Classification Key | R220 |
| List of Characteristics | NC82 |
| Metals Coefficient | -----71 |
| Packaging Length | 455,00 |
| Packaging Width | 255,00 |
| Packaging Height | 275,00 |
| Packaging Size | MM |
| Product Code | 4R43 |
| Comparative Metals Coefficient | 01.06.2019 |
| Unit of Measure | ST |
| Article Number | 1FK23064AC000MB0 |
| Product Family | 1FK2 for SINAMICS S120 |

| | |
|-------------------------------------|--------------------------|
| Product Group | 4R43 |
| Catalog ID | NC82 |
| Packaging Dimensions | 10.039 x 17.913 x 10.827 |
| Package Size Unit of Measure | Inch |
| Quantity Unit | 1 Piece |
| Voltage Rating | 480 V |
| Net Weight | 25.133 lb |
| Packaging Quantity | 1 pieces |
| Commodity Code | 85015220 |
| Power | 2.2 kW |
| Speed | 2000 rpm |
| Tightening Torque | 12 Nm |
| IP Rating | IP64 |