

3LD2064-1TC51

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3ld2064-1tc51 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|--|
| Weight | 0.45 kgs |
| Unit of Measure | ST |
| AL Field | N |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85365080 |
| Copper Weight | 0 |
| EAN | 4011209512139.0 |
| Quantity in Package | 1 |
| Product Code | 5887 |
| UPC | 804766153587.0 |
| Compliance | Produkt zgodny z RoHS od: 01.01.2003 |
| ETIM 7 | EC000216 |
| Packaging Width | 105,00 |
| Configurable Product | False |
| eClass 6 | 27-37-14-03 |
| eClass 7.1 | 27-37-14-03 |
| eClass 8 | 27-37-14-03 |
| eClass Version 9 | 27-37-14-03 |
| eClass Version 9.1 | 27-37-14-03 |
| Product ID | 3LD2064-1TC51 |
| Country of Origin | DE |
| ECCN | N |
| Group Classification Key | P360 |
| List of Characteristics | LV10.1 |
| Metals Coefficient | LA0----- |
| Packaging Length | 163,00 |
| Packaging Height | 122,00 |
| Packaging Size | MM |
| Product Description | 4-BIEG. ROZŁĄCZNIK GŁÓWNY / AWARYJNY Z ZACISKIEM PE; MOC: 7.5kW /AC23 A; 5.5kW /AC-3; PRĄD: IU=16A/ AC-21A W OBUDOWIE Z TWORZYWA Z CZARNYM NAPĘDEM OBROTOWYM Z MOŻLIWOŚCIĄ BLOKOWANIA W POZYCJI 0 NA 3 KŁÓDKI |
| Comparative Metals Coefficient | 01.01.2003 |