

### 3LD2165-7UB01

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 3ld2165-7ub01                    |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |   |
|--------------------------------|---|
| AL Field                       | N   |
| ECCN                           | N   |
| Aluminium Weight               | 0   |
| Argent Weight                  | 0   |
| Customs Tariff Code            | 85365080  |
| Copper Weight                  | 0   |
| EAN                            | 4011209492899.0   |
| Quantity in Package            | 1   |
| Product Code                   | 5887  |
| UPC                            | 754554928487.0  |
| Weight                         | 882   |
| eClass 7.1                     | 27-37-14-03   |
| eClass 8                       | 27-37-14-03   |
| ETIM 7                         | EC000216  |
| eClass Version 9               | 27-37-14-03   |
| eClass Version 9.1             | 27-37-14-03   |
| Metals Coefficient             | LA0-----  |
| Packaging Length               | 202,00  |
| Packaging Size                 | MM  |
| Product Description            | 3-BIEG. ROZŁĄCZNIK GŁÓWNY / AWARYJNY Z DWOMA ZCISKAMI N; MOC: 9.5kW /AC23 A; 7.5kW /AC-3; PRĄD: IU=25A/ AC-21A MONTAŻ TABLICOWY NA OTWÓR CENTRALNY 22,5 MM Z CZARNYM POKRĘTŁEM Z MOŻLIWOŚCIĄ BLOKOWANIA W POZYCJI 0 LUB 1 NA 2 KLÓDKI |
| Comparative Metals Coefficient | 01.01.2003  |
| List of Characteristics        | LV10.1  |
| Packaging Width                | 153,00  |
| Packaging Height               | 149,00  |
| Unit of Measure                | ST  |
| Product ID                     | 3LD2165-7UB01   |
| Compliance                     | Produkt zgodny z RoHS od: 01.01.2003  |
| Country of Origin              | DE  |
| Configurable Product           | False   |
| eClass 6                       | 27-37-14-03   |
| Group Classification Key       | P360  |