

3LD2217-1TL11

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3ld2217-1tl11 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|--|
| Weight | 0.45 kgs |
| ECCN | N |
| Packaging Width | 85,00 |
| Unit of Measure | ST |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85365080 |
| Copper Weight | 0 |
| EAN | 4011209718630.0 |
| Quantity in Package | 1 |
| Product Code | 5887 |
| UPC | 662643677522.0 |
| List of Characteristics | LV10.1 |
| Packaging Length | 460,00 |
| ETIM 7 | EC000216 |
| Packaging Height | 70,00 |
| Comparative Metals Coefficient | 15.03.2005 |
| Compliance | Produkt zgodny z RoHS od: 15.03.2005 |
| Country of Origin | DE |
| Product ID | 3LD2217-1TL11 |
| Configurable Product | False |
| eClass 6 | 27-37-14-03 |
| eClass 7.1 | 27-37-14-03 |
| Packaging Size | MM |
| Product Description | 4-BIEG. ROZŁĄCZNIK GŁÓWNY / AWARYJNY; MOC: 11.5kW /AC23 A; 9.5kW /AC-3; PRĄD: IU=32A/ AC-21A MONTAŻ NA PŁYCY LUB SZYNIE 35 MM Z CZARNYM NAPĘDEM OBROTOWYM DRZWIOWYM MOCOWANYM NA 4 OTWORY Z MOŻLIWOŚCIĄ BLOKOWANIA W POZYCJI 0 NA 3 KŁÓDKI |
| eClass 8 | 27-37-14-03 |
| eClass Version 9 | 27-37-14-03 |
| eClass Version 9.1 | 27-37-14-03 |
| Group Classification Key | P360 |
| Metals Coefficient | LA0----- |
| AL Field | N |