

3LD2265-8VQ51-0AF6

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3ld2265-8vq51-0af6 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|--|
| ECCN | N |
| Unit of Measure | ST |
| List of Characteristics | LV10.1 |
| Packaging Height | 149,00 |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85365080 |
| AL Field | N |
| Copper Weight | 0 |
| EAN | 4011209791541.0 |
| Quantity in Package | 1 |
| Product Code | 5887 |
| Weight | 948 |
| Compliance | Produkt zgodny z RoHS od: 23.10.2008 |
| Configurable Product | False |
| eClass 6 | 27-37-14-03 |
| eClass 7.1 | 27-37-14-03 |
| eClass 8 | 27-37-14-03 |
| eClass Version 9 | 27-37-14-03 |
| eClass Version 9.1 | 27-37-14-03 |
| Group Classification Key | P360 |
| Metals Coefficient | LA0----- |
| Packaging Width | 152,00 |
| Product ID | 3LD2265-8VQ51-0AF6 |
| ETIM 7 | EC000216 |
| Comparative Metals Coefficient | 23.10.2008 |
| Country of Origin | DE |
| Packaging Length | 202,00 |
| Packaging Size | MM |
| Product Description | 2 BIEG. ROZŁĄCZNIK GŁÓWNY / AWARYJNY Z DWOMA ZCISKAMI N; 800V DC DC21 32A, DC22 16A W OBUDOWIE Z TWORZYWA Z CZARNYM NAPĘDEM OBROTOWYM Z MOŻLIWOŚCIĄ BŁOKOWANIA W POZYCJI 0 NA 3 KLÓDKI |