

3LD24300TK11

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3ld24300tk11 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|--|
| Product ID | 3LD2430-0TK11 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 06.12.2008 |
| Configurable Product | False |
| Country of Origin | DE |
| ECCN | N |
| ETIM 7 | EC000216 |
| Group Classification Key | P360 |
| List of Characteristics | LV10.1 |
| Metals Coefficient | LA0----- |
| Packaging Size | MM |
| Product Description | 3-BIEG. ROZŁĄCZNIK GŁÓWNY / AWARYJNY; MOC: 132kW /AC23 A; 110kW /AC-3; PRĄD: IU=250A/ AC-21A MONTAŻ MODUŁOWY WEWNĄTRZ ROZDZIELNICY NA ŚRUBY Z CZARNYM POKRĘTŁEM Z MOŻLIWOŚCIĄ BLOKOWANIA W POZYCJI 0 NA 3 KŁÓDKI |
| Unit of Measure | ST |
| Weight | 2030 kg |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85365080 |
| Copper Weight | 0 |
| EAN | 4011209786981.0 |
| eClass 6 | 27-37-14-03 |
| eClass 7.1 | 27-37-14-03 |
| eClass 8 | 27-37-14-03 |
| eClass Version 9 | 27-37-14-03 |
| eClass Version 9.1 | 27-37-14-03 |
| Quantity in Package | 1 |
| Packaging Length | 314,00 |
| Packaging Width | 222,00 |
| Packaging Height | 195,00 |
| Product Code | 5887 |
| Comparative Metals Coefficient | 06.12.2008 |
| UPC | 40892595499.0 |

Description

3-pole main/emergency switch with a power rating of 132kW/AC23 A and 110kW/AC-3. The rated current is $I_U=250A/AC-21A$. Designed for modular installation inside a distribution board, featuring a black knob that allows locking in the 0 position with 3 padlocks. Compliant with RoHS since 06.12.2008, manufactured in Germany. Weight is 1.81 kg, and packaging dimensions are 314x222x195 mm.