

3LD3248-0TL51

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3ld3248-0tl51 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|---|
| Customs Tariff Code | 85365080 |
| EAN | 4001869551036.0 |
| Quantity in Package | 1 |
| Product Code | 5887 |
| Weight | 385 |
| Product ID | 3LD3248-0TL51 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 01.09.2006 |
| Configurable Product | False |
| Country of Origin | DE |
| ECCN | N |
| eClass 6 | 27-37-14-03 |
| eClass 7.1 | 27-37-14-03 |
| eClass 8 | 27-37-14-03 |
| eClass Version 9 | 27-37-14-03 |
| eClass Version 9.1 | 27-37-14-03 |
| ETIM 7 | EC000216 |
| Group Classification Key | P360 |
| List of Characteristics | LV10 |
| Packaging Length | 83,00 |
| Packaging Width | 68,00 |
| Packaging Height | 420,00 |
| Packaging Size | MM |
| Product Description | Rozłącznik izolacyjny 3LD3, Iu 32 A wyłącznik główny 3-biegunowy + N Znamionowa moc robocza przy AC-23 A przy 400V 11,5kW mocowanie do podłoża wyłącznik podstawowy ze sprzęgłem mocowanie w otworze centralnym 22,5mm napęd obrotowy czarny 66 x 66 mm |
| Comparative Metals Coefficient | 01.09.2006 |
| Unit of Measure | ST |
| Article Number | 3LD32480TL51 |
| Product Family | Ordering Data Overview |
| Catalog ID | LV10 |
| Packaging Dimensions | 2.677 x 3.268 x 16.535 |
| Package Size Unit of Measure | Inch |
| Quantity Unit | 1 Piece |
| Current Rating | 32, 23 A |

| | |
|-----------------------------|----------|
| Voltage Rating | 400 V |
| Product Group | 5887 |
| Net Weight | 0.849 lb |
| Packaging Quantity | 1 pieces |
| Commodity Code | 85365080 |
| Power | 11.5 kW |
| Number of Poles | 3 |
| Utilization Category | AC-23 |