

### 3LD3340-0TL11

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3ld3340-0tl11
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>EAN</b>	4001869551388.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	5887
<b>Weight</b>	367
<b>AL Field</b>	N
<b>Customs Tariff Code</b>	85365080
<b>Product ID</b>	3LD3340-0TL11
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.09.2006
<b>Configurable Product</b>	False
<b>ECCN</b>	N
<b>eClass 6</b>	27-37-14-03
<b>eClass 7.1</b>	27-37-14-03
<b>eClass 8</b>	27-37-14-03
<b>eClass Version 9</b>	27-37-14-03
<b>eClass Version 9.1</b>	27-37-14-03
<b>ETIM 7</b>	EC000216
<b>Group Classification Key</b>	P360
<b>List of Characteristics</b>	LV10
<b>Packaging Length</b>	83,00
<b>Packaging Width</b>	68,00
<b>Packaging Height</b>	420,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	Rozłącznik izolacyjny 3LD3, Iu 40 A wyłącznik główny 3-biegunowy + N Znamionowa moc robocza przy AC-23 A przy 400V 18,5kW mocowanie do podłoża wyłącznik podstawowy ze sprzęgłem mocowanie w otworze centralnym 22,5mm napęd pokrętkiem czarny 48x48 mm
<b>Comparative Metals Coefficient</b>	01.09.2006
<b>Unit of Measure</b>	ST
<b>Country of Origin</b>	DE
<b>Article Number</b>	3LD33400TL11
<b>Product Family</b>	Ordering Data Overview
<b>Catalog ID</b>	LV10
<b>Packaging Dimensions</b>	2.677 x 3.268 x 16.535
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Current Rating</b>	40, 23 A

<b>Voltage Rating</b>	400 V
<b>Product Group</b>	5887
<b>Net Weight</b>	0.809 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85365080
<b>Power</b>	18.5 kW
<b>Number of Poles</b>	3
<b>Utilization Category</b>	AC-23