

### 3LD33540TK53

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 3ld33540tk53                     |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Legacy / discontinued            |

## Technical specification

|                                |   |
|--------------------------------|---|
| Customs Tariff Code            | 85365080  |
| EAN                            | 4001869551616.0   |
| Quantity in Package            | 1   |
| Product Code                   | 5887  |
| Weight                         | 238   |
| Packaging Size                 | MM  |
| Product ID                     | 3LD3354-0TK53   |
| AL Field                       | N   |
| Compliance                     | Produkt zgodny z RoHS od: 01.09.2006  |
| Configurable Product           | False   |
| Country of Origin              | DE  |
| ECCN                           | N   |
| eClass 6                       | 27-37-14-03   |
| eClass 7.1                     | 27-37-14-03   |
| eClass 8                       | 27-37-14-03   |
| eClass Version 9               | 27-37-14-03   |
| eClass Version 9.1             | 27-37-14-03   |
| ETIM 7                         | EC000216  |
| Group Classification Key       | P360  |
| List of Characteristics        | LV10  |
| Packaging Length               | 85,00   |
| Packaging Width                | 79,00   |
| Packaging Height               | 110,00  |
| Product Description            | Rozłącznik izolacyjny 3LD3, Iu 40 A wyłącznik główny 3-biegunowy Znamionowa moc robocza przy AC-23 A przy 400V 18,5kW mocowanie frontowe, wyłącznik podstawowy z mocowanie w otworze centralnym 22,5mm napęd pokrętkiem czerwony/żółty 66x66 mm |
| Comparative Metals Coefficient | 01.09.2006  |
| Unit of Measure                | ST  |
| Article Number                 | 3LD33540TK53  |
| Product Family                 | Ordering Data Overview  |
| Catalog ID                     | LV10  |
| Packaging Dimensions           | 3.11 x 3.346 x 4.331  |
| Package Size Unit of Measure   | Inch  |
| Quantity Unit                  | 1 Piece   |
| Current Rating                 | 40, 23 A  |

|                             |          |
|-----------------------------|----------|
| <b>Voltage Rating</b>       | 400 V    |
| <b>Product Group</b>        | 5887     |
| <b>Net Weight</b>           | 0.518 lb |
| <b>Packaging Quantity</b>   | 1 pieces |
| <b>Commodity Code</b>       | 85365080 |
| <b>Power</b>                | 18.5 kW  |
| <b>Number of Poles</b>      | 3        |
| <b>Utilization Category</b> | AC-23    |

## Description

Load disconnecter 3LD3, Iu 40 A Main switch 3-pole Rated operating capacity at AC-23 A at 400 V 18.5 kW Front plate mounting Basic switch with Central hole mounting 22.5mm Toggle drive red / yellow 66x66 mm