

### 3LD9220-0C

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3ld9220-0c
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.02 kgs
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85365080
<b>Copper Weight</b>	0
<b>EAN</b>	4011209403970.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	5887
<b>Product ID</b>	3LD9220-0C
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.01.2003
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>ECCN</b>	N
<b>eClass 6</b>	27-37-92-01
<b>eClass 7.1</b>	27-37-92-01
<b>eClass 8</b>	27-37-92-01
<b>eClass Version 9</b>	27-37-92-01
<b>eClass Version 9.1</b>	27-37-92-01
<b>ETIM 7</b>	EC002498
<b>Group Classification Key</b>	P360
<b>List of Characteristics</b>	LV10.1
<b>Metals Coefficient</b>	L-0-----
<b>Packaging Length</b>	55,00
<b>Packaging Width</b>	41,00
<b>Packaging Height</b>	21,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	DODATKOWY STYK BIEGUNA N (DLA 3LD21/22 DO MONTAŻU NA PŁYCIĘ LUB SZYNIĘ 35 MM ALBO W ZABUDOWIE MODUŁOWEJ WEWNĄTRZ ROZDZIELNICY)
<b>Comparative Metals Coefficient</b>	01.01.2003
<b>Unit of Measure</b>	ST