

### 3NA3260

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3na3260
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.29 kgs
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85361090
<b>Copper Weight</b>	0
<b>EAN</b>	4001869056401.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	5530
<b>Product ID</b>	3NA3260
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.09.2006
<b>Configurable Product</b>	False
<b>Country of Origin</b>	GR
<b>ECCN</b>	N
<b>eClass 6</b>	27-14-20-05
<b>eClass 7.1</b>	27-14-20-05
<b>eClass 8</b>	27-14-20-05
<b>eClass Version 9</b>	27-14-20-05
<b>eClass Version 9.1</b>	27-14-20-05
<b>ETIM 7</b>	EC000055
<b>Group Classification Key</b>	P310
<b>List of Characteristics</b>	LV10.1
<b>Metals Coefficient</b>	L-P-----
<b>Packaging Length</b>	185,00
<b>Packaging Width</b>	158,00
<b>Packaging Height</b>	77,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	WKŁADKA TOPIKOWA NH, 500V, WLK. 2, 400A, KLASA gG, WERSJA STANDARD, ZACZEPY NIEIZOLOWANE,
<b>Comparative Metals Coefficient</b>	01.09.2006
<b>Unit of Measure</b>	ST
<b>UPC</b>	754554233383
<b>Article Number</b>	3NA3260
<b>Product Family</b>	Ordering Data Overview
<b>Catalog ID</b>	LV10.1

<b>Packaging Dimensions</b>	6.22 x 7.283 x 3.031
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Voltage Rating AC</b>	500 V
<b>Voltage Rating DC</b>	440 V
<b>Product Group</b>	5530
<b>Net Weight</b>	1.418 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85361090
<b>Current Rating</b>	400 A
<b>NH Size</b>	2
<b>Fuse Characteristic</b>	GG