

### 3NA6814-4

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 3na6814-4                        |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                       |  |
|---------------------------------------|--|
| <b>Weight</b>                         | 0.15 kgs   |
| <b>Aluminium Weight</b>               | 0  |
| <b>Argent Weight</b>                  | 0  |
| <b>Customs Tariff Code</b>            | 85361050   |
| <b>Copper Weight</b>                  | 0  |
| <b>EAN</b>                            | 4001869216669.0  |
| <b>Quantity in Package</b>            | 1  |
| <b>Product Code</b>                   | 5530   |
| <b>eClass 7.1</b>                     | 27-14-20-05  |
| <b>Product ID</b>                     | 3NA6814-4  |
| <b>AL Field</b>                       | N  |
| <b>Compliance</b>                     | Produkt zgodny z RoHS od: 01.10.2006   |
| <b>Configurable Product</b>           | False  |
| <b>Country of Origin</b>              | GR   |
| <b>ECCN</b>                           | N  |
| <b>eClass 6</b>                       | 27-14-20-05  |
| <b>eClass 8</b>                       | 27-14-20-05  |
| <b>eClass Version 9</b>               | 27-14-20-05  |
| <b>eClass Version 9.1</b>             | 27-14-20-05  |
| <b>ETIM 7</b>                         | EC000055   |
| <b>Group Classification Key</b>       | P310   |
| <b>List of Characteristics</b>        | LV10.1   |
| <b>Metals Coefficient</b>             | L-P-----   |
| <b>Packaging Length</b>               | 84,00  |
| <b>Packaging Width</b>                | 65,00  |
| <b>Packaging Height</b>               | 62,00  |
| <b>Packaging Size</b>                 | MM   |
| <b>Product Description</b>            | WKŁADKA TOPIKOWA NH, 400V, WLK. 000, 35A, KLASA gG, Z PASKOWYM SYGN. PRZEPALENIA, ZACZEPY IZOLOWANE, |
| <b>Comparative Metals Coefficient</b> | 01.10.2006   |
| <b>Unit of Measure</b>                | ST   |