

### 3RA2120-4BE26-0BB4

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3ra2120-4be26-0bb4
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Product Description	BEZBEZP. UKŁ. ZASILANIA, ROZRUCH BEZPOŚREDNI, AC 400V, WIELKOŚĆ S0, 14. . .20A, DC 24V PRZYŁ. SPRĘŻYNOWE, NA SZYNE DIN, TYP KOORDYNACJI 1, IQ = 150KA 1N0+1NC (STYCZNIK)
Product Code	5348
Comparative Metals Coefficient	01.10.2009
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST
UPC	662643900309.0
Weight	1150
Product ID	3RA2120-4BE26-0BB4
AL Field	N
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85364900
Compliance	Produkt zgodny z RoHS od: 01.10.2009
Configurable Product	False
Copper Weight	0
Country of Origin	DE
EAN	4011209795174.0
ECCN	N
eClass 6	27-37-09-05
eClass 7.1	27-37-09-05
eClass 8	27-37-09-05
eClass Version 9	27-37-09-05
eClass Version 9.1	27-37-09-05
ETIM 7	EC001037
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LC0-----
Quantity in Package	1
Packaging Length	252,50
Packaging Width	60,50
Packaging Height	118,50
Packaging Size	MM

## Description

Load feeder fuseless, Direct-on-line starting 400 V AC, Size S0 13...20 A 24 V DC  
Spring-type terminal for installation on standard mounting rail Type of coordination 1,  
Iq = 150 kA 1 NO+1 NC (contactor)