

### 3RA6120-0CB30

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3ra6120-0cb30
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.62 kgs
<b>Product Description</b>	SIRIUS, KOMPAKTOWY ZESTAW ROZRUCHOWY, ROZRUCH BEZPOŚREDNI 690 V, 24 V AC/DC, 50 ... 60 HZ, 1 ... 4 A, IP20, RODZAJ ZACISKÓW OBWODU GŁÓWNEGO: WTYKOWE, BEZ ZACISKÓW, RODZAJ ZACISKÓW OBWODU POMOCNICZEGO: WTYKOWE, BEZ ZACISKÓW
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85364900
<b>Copper Weight</b>	0
<b>EAN</b>	4011209778580.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	5341
<b>Comparative Metals Coefficient</b>	01.05.2012
<b>Product ID</b>	3RA6120-0CB30
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.05.2012
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>ECCN</b>	N
<b>eClass 6</b>	27-37-09-05
<b>eClass 7.1</b>	27-37-09-05
<b>eClass 8</b>	27-37-09-05
<b>eClass Version 9</b>	27-37-09-05
<b>eClass Version 9.1</b>	27-37-09-05
<b>ETIM 7</b>	EC001037
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Metals Coefficient</b>	LC0-----
<b>Packaging Length</b>	228,50
<b>Packaging Width</b>	181,50
<b>Packaging Height</b>	59,50
<b>Packaging Size</b>	MM
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236; Lead titanium zirconium oxide lblREACHCasNo0830
<b>Unit of Measure</b>	ST