3RA61201EP32

Industrial automation components

Add to quote

Ask about this product



Manufacturer	Siemens
Catalog number	3ra61201ep32
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Voltage Rating	690 V
Input Voltage Range	110 to 240 V AC/DC
Current Rating	8 to 32 A
Enclosure Type	IP20
Terminal Type	Screw-type terminals

Description

The Siemens 3RA61201EP32 is a SIRIUS Compact load feeder direct-on-line (DOL) starter designed for efficient motor control in industrial applications. Operating at a voltage rating of 690 V and supporting input voltages between 110 to 240 V AC/DC, it accommodates current ratings from 8 to 32 A.

This starter is housed in an IP20 enclosure, ensuring protection against solid objects larger than 12 mm. It features screw-type terminals for both main and auxiliary circuits, facilitating secure and reliable connections.

The device operates within a temperature range of -20°C to 60°C, making it suitable for various industrial environments. Its compact design allows for space-saving installation in control cabinets, and it is engineered to prevent main contact welding, enhancing the longevity and reliability of the motor control system.

The 3RA61201EP32 is part of Siemens' SIRIUS series, known for integrating motor starter protection, contactor, and overload relay functions into a single unit, streamlining motor control and protection processes.

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE
VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.