

3RA6250-1BB32

Industrial automation components

Manufacturer	Siemens
Catalog number	3ra6250-1bb32
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	2.72 kgs
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85364900
Copper Weight	0
EAN	4011209715165.0
Quantity in Package	1
Packaging Height	109,50
Packaging Size	MM
Product Description	SIRIUS, KOMPAKTOWY ZESTAW ROZRUCHOWY, ROZRUCH NAWROTNY 690 V, 24 V AC/DC, 50 ... 60 HZ, 0.32 ... 1.25 A, IP20, RODZAJ ZACISKÓW OBWODU GŁÓWNEGO: ZACISKI ŚRUBOWE, RODZAJ ZACISKÓW OBWODU POMOCNICZEGO: ZACISKI ŚRUBOWE
Product Code	5341
Comparative Metals Coefficient	01.05.2012
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST
eClass 7.1	27-37-09-05
eClass 8	27-37-09-05
eClass Version 9	27-37-09-05
eClass Version 9.1	27-37-09-05
ETIM 7	EC001037
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LC0-----
Packaging Length	228,00
Packaging Width	183,00
Product ID	3RA6250-1BB32
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	DE
ECCN	N
eClass 6	27-37-09-05

Description

3RA6250-1BB32 | Siemens, Reversing Starter, 0.37 kW @ 400 V ac, 690 V ac, 1.25 A, 3 Phase, Screw Terminal, 170 x 90 x 165 mm | Brand / Manufacturer: Siemens | product type: Reversing Starter | type of motor starter: Reversing Starter | power classification: 0.37 kW @ 400 V ac | control voltage: 690 V ac | current rating: 1.25 A | phase: 3 | minimum operating frequency: 50 Hz | maximum operating frequency: 60 Hz | type of attachment: DIN Rail Mount;Snap-On Mount | voltage on terminals: Screw