

3RA62501AB32

Industrial automation components

Manufacturer	Siemens
Catalog number	3ra62501ab32
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Aluminium Weight	0
Weight	2552 kg
Argent Weight	0
Customs Tariff Code	85364900
Copper Weight	0
EAN	4011209714953.0
eClass 6	27-37-09-05
eClass 7.1	27-37-09-05
eClass 8	27-37-09-05
eClass Version 9	27-37-09-05
eClass Version 9.1	27-37-09-05
Quantity in Package	1
Packaging Length	228,00
Packaging Width	183,00
Packaging Height	109,50
Product Code	5341
Comparative Metals Coefficient	01.05.2012
Product ID	3RA6250-1AB32
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	DE
ECCN	EAR99
ETIM 7	EC001037
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LC0-----
Packaging Size	MM
Product Description	SIRIUS, KOMPAKTOWY ZESTAW ROZRUCHOWY, ROZRUCH NAWROTNY 690 V, 24 V AC/DC, 50 ... 60 HZ, 0.1 ... 0.4 A, IP20, RODZAJ ZACISKÓW OBWODU GŁÓWNEGO: ZACISKI ŚRUBOWE, RODZAJ ZACISKÓW OBWODU POMOCNICZEGO: ZACISKI ŚRUBOWE
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST

Description

SIRIUS, a compact starter set designed for reversing start with a voltage of 690 V and 24 V AC/DC, operating at frequencies of 50 ... 60 Hz and a current range of 0.1 ... 0.4 A. The product features an IP20 protection rating and screw terminals for both main and auxiliary circuits. Compliant with RoHS since 01.05.2012, the product is not configurable. The weight is 2.72 kg, and the packaging dimensions are 228 x 183 x 109.5 mm. Country of origin: Germany.