

### 3RF2420-1AB45

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rf2420-1ab45
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.45 kgs
<b>Product ID</b>	3RF2420-1AB45
<b>AL Field</b>	N
<b>Customs Tariff Code</b>	85364900
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.07.2006
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>EAN</b>	4011209646919.0
<b>ECCN</b>	EAR99
<b>eClass 6</b>	27-37-10-14
<b>eClass 7.1</b>	27-37-10-14
<b>eClass 8</b>	27-37-10-14
<b>eClass Version 9</b>	27-37-10-14
<b>eClass Version 9.1</b>	27-37-10-14
<b>ETIM 7</b>	EC002055
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	112,00
<b>Packaging Width</b>	76,00
<b>Packaging Height</b>	131,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	STYCZNIK PÓŁPRZEWODNIKOWY 3-FAZ. 3RF2, AC 51 20A 40 ST. C, 48-600V / 4-30V DC, STER. 2-FAZOWE, PRZYŁ. ŚRUBOWE NAP. BLOKUJĄCE 1200V
<b>Product Code</b>	3725
<b>Comparative Metals Coefficient</b>	01.07.2006
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Dibutylbis(pentane-2,4-dionato-0,0')tin CAS-No. 22673-19-4
<b>Unit of Measure</b>	ST
<b>UPC</b>	40892553970.0