

3RH21221SB40

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3rh21221sb40 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Legacy / discontinued |

Technical specification

| | |
|--------------------------------|---|
| Weight | 0.45 kgs |
| Product ID | 3RH2122-1SB40 |
| AL Field | N |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85364900 |
| Compliance | Produkt zgodny z RoHS od: 01.10.2009 |
| Configurable Product | False |
| Copper Weight | 0 |
| Country of Origin | DE |
| EAN | 4011209846739.0 |
| ECCN | N |
| eClass 6 | 27-37-10-01 |
| eClass 7.1 | 27-37-10-01 |
| eClass 8 | 27-37-10-01 |
| eClass Version 9 | 27-37-10-01 |
| eClass Version 9.1 | 27-37-10-01 |
| ETIM 7 | EC000196 |
| Group Classification Key | R711 |
| List of Characteristics | CC-IC10 |
| Metals Coefficient | LBP----- |
| Quantity in Package | 1 |
| Packaging Length | 61,50 |
| Packaging Width | 50,00 |
| Packaging Height | 77,50 |
| Packaging Size | MM |
| Product Description | STYCZNIK SPRZĘGAJĄCY, 2N0+2NC DC 24V, 0.85...1.85*US, Z DIODĄ TŁUMIĄCĄ, ROZMIAR S00, POŁĄCZENIE ŚRUBOWE |
| Product Code | 5331 |
| Comparative Metals Coefficient | 01.10.2009 |
| REACH | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368 |
| Unit of Measure | ST |
| UPC | 662643903539.0 |

Description

Coupling contactor relay, 2 NC+2 NO 24 V DC, 0.85-1.85*US with integrated suppressor diode Size S00 screw terminal