

3RH2271-1BB40

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3rh2271-1bb40 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|---|
| Weight | 0.45 kgs |
| Product ID | 3RH2271-1BB40 |
| AL Field | N |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85364900 |
| Compliance | Produkt zgodny z RoHS od: 01.10.2009 |
| Configurable Product | False |
| Copper Weight | 0 |
| Country of Origin | DE |
| EAN | 4011209947443.0 |
| ECCN | N |
| eClass 6 | 27-37-10-01 |
| eClass 7.1 | 27-37-10-01 |
| eClass 8 | 27-37-10-01 |
| eClass Version 9 | 27-37-10-01 |
| eClass Version 9.1 | 27-37-10-01 |
| ETIM 7 | EC000196 |
| Group Classification Key | R711 |
| List of Characteristics | CC-IC10 |
| Metals Coefficient | LBP----- |
| Quantity in Package | 1 |
| Packaging Length | 61,50 |
| Packaging Width | 50,00 |
| Packaging Height | 120,50 |
| Packaging Size | MM |
| Product Description | stycznik pomocniczy, 7 NO + 1 NC, DC 24 V, wielkość S00, przyłącze śrubowe, łącznik pomocniczy zamontowany na stałe |
| Product Code | 5331 |
| Comparative Metals Coefficient | 01.10.2009 |
| Unit of Measure | ST |
| UPC | 887621425395.0 |