

### 3RK1105-1BG04-2CA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rk1105-1bg04-2ca0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.45 kgs
Product ID	3RK1105-1BG04-2CA0
Notes	Wycofanie produktu od: 01.10.2022 Zmiana na F-CM AS-i Safety ST (3RK7136-6SC00-0BC1) plus F-DQ ET 200S
AL Field	N
Customs Tariff Code	85364900
Compliance	Produkt zgodny z RoHS od: 01.07.2006
Configurable Product	False
Country of Origin	CZ
EAN	4011209718883.0
ECCN	N
eClass 6	27-24-26-08
eClass 7.1	27-24-26-08
eClass 8	27-24-26-08
eClass Version 9	27-24-26-08
eClass Version 9.1	27-24-26-08
ETIM 7	EC001604
Group Classification Key	R711
List of Characteristics	CC-IC10
Quantity in Package	1
Packaging Length	57,00
Packaging Width	113,00
Packaging Height	131,00
Packaging Size	MM
Product Code	3720
Comparative Metals Coefficient	01.07.2006
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST
UPC	754554956985.0

## Description

ASISafe extended Safety monitor 2 F-R0 2 enabling circuits IP20, with spring-type terminal removable terminals Safe output relay Response time maximum 40 ms Monitor type 4, Version 3 Can be used up to Category 4 (EN954-1) up to PL E (EN ISO 13849-1) up to SIL 3 (IEC 61508)