

3RK1304-5KS40-2AA0

Industrial automation components

Manufacturer	Siemens
Catalog number	3rk1304-5ks40-2aa0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	1.81 kgs
eClass Version 9	27-37-09-05
eClass 8	27-37-09-05
Product ID	3RK1304-5KS40-2AA0
AL Field	N
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Copper Weight	0
Country of Origin	DE
EAN	4011209659926.0
ECCN	N
eClass 6	27-37-09-05
eClass 7.1	27-37-09-05
eClass Version 9.1	27-37-09-05
ETIM 7	EC001037
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Quantity in Package	1
Packaging Length	309,00
Packaging Width	228,00
Packaging Height	184,00
Packaging Size	MM
Product Description	ET 200PRO DSE HF HIGH FEATURE, ROZRUCH BEZPOŚREDNI, ŁĄCZENIE MECHANICZNE, ELEKTRONICZNA OCHRONA UE 3PH 400 V/0.9KW; 0.15A...2.00A BEZ STYKU HAMUJĄCEGO 4DI 24 V DC; HAN Q4/2 - HAN Q8/0
Product Code	3723
Comparative Metals Coefficient	01.05.2012
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST
UPC	662643243611.0

Description

3RK1304-5KS40-2AA0 | Siemens, DOL Starter, 900 W, 0.3 to 3 A, 200 to 440 V ac, Plug-In Mount | Brand / Manufacturer: Siemens | product type: DOL Starter | series: ET 200pro | power classification: 900 W | current rating: 0.3 to 3 A | rated voltage: 200 to 440 V ac | type of attachment: Plug-In Mount | length: 65 mm | width: 150 mm | height: 290 mm | minimum operating temperature: 0 °C | maximum working temperature: +60 °C