

### 3RK1304-5KS40-4AA3

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rk1304-5ks40-4aa3
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.82 kgs
<b>Product ID</b>	3RK1304-5KS40-4AA3
<b>AL Field</b>	N
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85371098
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.05.2012
<b>Configurable Product</b>	False
<b>Copper Weight</b>	0
<b>Country of Origin</b>	DE
<b>EAN</b>	4011209659902.0
<b>ECCN</b>	N
<b>eClass 6</b>	27-37-09-05
<b>eClass 7.1</b>	27-37-09-05
<b>eClass 8</b>	27-37-09-05
<b>eClass Version 9</b>	27-37-09-05
<b>eClass Version 9.1</b>	27-37-09-05
<b>ETIM 7</b>	EC001037
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Metals Coefficient</b>	LA0-----
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	309,00
<b>Packaging Width</b>	228,00
<b>Packaging Height</b>	184,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	ET 200PRO DSE ST STANDARD, ROZRUCH BEZPOŚREDNI, ŁĄCZENIE MECHANICZNE, ELEKTRONICZNA OCHRONA UE 3PH 400 V/0.9Kw; 0.15A...2.00A BRAKE CONTACT AC 400V; HAN Q4/2 - HAN Q8/0
<b>Product Code</b>	3723
<b>Comparative Metals Coefficient</b>	01.05.2012
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236; Lead titanium zirconium oxide lblREACHCasNo0830
<b>Unit of Measure</b>	ST
<b>UPC</b>	662643393712.0

## Description

3RK1304-5KS40-4AA3 | Siemens, DOL Starter, 200 to 400 V, 2 A, 900 W, Screw Mount | Brand / Manufacturer: Siemens | mass: 1.7 | product type: DOL Starter | power classification: 900 W | current rating: 2 A | rated voltage: 200 to 400 V | type of attachment: Screw Mount | length: 110 mm | width: 150 mm | height: 230 mm | minimum operating temperature: -25 °C