

3RK1304-5KS70-3AA3

Industrial automation components

Manufacturer	Siemens
Catalog number	3rk1304-5ks70-3aa3
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Product ID	3RK1304-5KS70-3AA3
AL Field	N
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Copper Weight	0
Country of Origin	DE
EAN	4011209680524.0
ECCN	N
eClass 6	27-37-09-05
eClass 7.1	27-37-09-05
eClass 8	27-37-09-05
eClass Version 9	27-37-09-05
eClass Version 9.1	27-37-09-05
ETIM 7	EC001037
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Quantity in Package	1
Packaging Length	236,50
Packaging Width	117,00
Packaging Height	190,50
Packaging Size	MM
Product Code	3723
Comparative Metals Coefficient	01.05.2012
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST
UPC	662643393750.0
Weight	1950

Description

3RK1304-5KS70-3AA3 | Siemens, Reversing Starter, 3 Phase, 0.15 to 2 A, 60 Hz, 110 x 160 x 246 mm | Brand / Manufacturer: Siemens | product type: Reversing Starter | type of motor starter: Reversing Starter | power classification: 900 W | control voltage: 200 to 400 V ac | current rating: 0.15 to 2 A | phase: 3 | minimum operating frequency: 50 Hz | maximum operating frequency: 60 Hz | type of attachment: Screw Mount | voltage on terminals: Tab | minimum operating temperature: -25 °C | maximum working temperature: +55 °C | Total length: 110 mm | total width: 160 mm | overall depth: 246 mm