

### 3RK1315-6KS41-3AA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rk1315-6ks41-3aa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Legacy / discontinued

## Technical specification

Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209823037.0
Quantity in Package	1
Product Code	3722
UPC	662643543964.0
Weight	4000
eClass 6	27-37-09-05
eClass 7.1	27-37-09-05
eClass 8	27-37-09-05
eClass Version 9	27-37-09-05
eClass Version 9.1	27-37-09-05
ETIM 7	EC001037
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Length	377,00
Packaging Width	287,00
Packaging Height	221,00
Comparative Metals Coefficient	01.07.2006
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236
Unit of Measure	ST
Product ID	3RK1315-6KS41-3AA0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.07.2006
Configurable Product	False
Country of Origin	DE
ECCN	N
Packaging Size	MM

## Description

SIRIUS motor starter M200D AS-i Communication: AS-Interface Reversing starter Basic  
Mechanical switching AC-3, 0.75KW / 400 V 0.15 A...2.00 A Electronic overload protection  
Thermistor: THERMOCLICK / PTC without brake contact 2DI AS-i + 2DI / 1DO on device Han  
Q4/2 - Han Q8/0 with manual on-site operation and key-operated switch