

3RK1315-6KS41-3AA3

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3rk1315-6ks41-3aa3 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|---|
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85371098 |
| Copper Weight | 0 |
| EAN | 4011209823044.0 |
| Quantity in Package | 1 |
| Product Code | 3722 |
| UPC | 662643543971.0 |
| Weight | 4080 |
| AL Field | N |
| eClass 7.1 | 27-37-09-05 |
| eClass 8 | 27-37-09-05 |
| eClass Version 9 | 27-37-09-05 |
| eClass Version 9.1 | 27-37-09-05 |
| ETIM 7 | EC001037 |
| Group Classification Key | R711 |
| List of Characteristics | CC-IC10 |
| Product ID | 3RK1315-6KS41-3AA3 |
| Compliance | Produkt zgodny z RoHS od: 01.07.2006 |
| Configurable Product | False |
| Country of Origin | DE |
| ECCN | EAR99 |
| eClass 6 | 27-37-09-05 |
| Metals Coefficient | LA0----- |
| Packaging Length | 377,00 |
| Packaging Width | 287,00 |
| Packaging Height | 221,00 |
| Packaging Size | MM |
| Comparative Metals Coefficient | 01.07.2006 |
| REACH | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236 |
| Unit of Measure | ST |

Description

3RK1315-6KS41-3AA3 | Siemens, Reversing Starter, 31.6 V dc, 0.15 to 2 A, Screw Mount, 294 x 159 x 215 mm | Brand / Manufacturer: Siemens | height: 377 | width: 287 | depth: 221 | mass: 4 | product type: Reversing Starter | rated voltage: 31.6 V dc | current rating: 0.15 to 2 A | phase: 3 | number of bars: 3 | power classification: 30 W | operating temperature range: -25 to +55 °C | type of attachment: Screw Mount | Size: 294 x 159 x 215 mm | requirements met: ISO 23570;CE Certified