

### 3RK13156NS712AA5

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 3rk13156ns712aa5                 |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |  |
|--------------------------------|--|
| Weight                         | 4061 kg  |
| Aluminium Weight               | 0  |
| Argent Weight                  | 0  |
| Customs Tariff Code            | 85371098   |
| Copper Weight                  | 0  |
| EAN                            | 4011209823341.0  |
| eClass 6                       | 27-37-09-05  |
| eClass 7.1                     | 27-37-09-05  |
| eClass 8                       | 27-37-09-05  |
| eClass Version 9               | 27-37-09-05  |
| eClass Version 9.1             | 27-37-09-05  |
| Quantity in Package            | 1  |
| Packaging Length               | 377,00   |
| Packaging Width                | 287,00   |
| Packaging Height               | 221,00   |
| Product Code                   | 3722   |
| Comparative Metals Coefficient | 01.07.2006   |
| UPC                            | 662643540291.0   |
| Product ID                     | 3RK1315-6NS71-2AA5   |
| AL Field                       | N  |
| Compliance                     | Produkt zgodny z RoHS od: 01.07.2006   |
| Configurable Product           | False  |
| Country of Origin              | DE   |
| ECCN                           | EAR99  |
| ETIM 7                         | EC001037   |
| Group Classification Key       | R711   |
| List of Characteristics        | CC-IC10  |
| Metals Coefficient             | LA0-----   |
| Packaging Size                 | MM   |
| REACH                          | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one lblREACHCasNo8105; lblREACHCode0236 lblREACHCasNo0236 |
| Unit of Measure                | ST   |

## Description

SIRIUS motor starter M200D AS-i Communication: AS-Interface DOL starter Basic Electronic switching AC-3, 4 kW / 400 V 1.5 A...9.00 A Electronic overload protection Thermistor: THERMOCLICK / PTC with brake contact 180 V DC 2DI AS-i + 2DI / 1DO on device Han Q4/2 - Han Q8/0 with manual on-site operation and key-operated switch