

3RK1325-6KS41-2AA0

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3rk1325-6ks41-2aa0 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Legacy / discontinued |

Technical specification

| | |
|--------------------------------|---|
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85371098 |
| Copper Weight | 0 |
| EAN | 4011209823471.0 |
| Quantity in Package | 1 |
| Product Code | 3722 |
| UPC | 662643543698.0 |
| Weight | 3680 |
| Packaging Size | MM |
| eClass Version 9 | 27-37-09-05 |
| Comparative Metals Coefficient | 01.07.2006 |
| eClass Version 9.1 | 27-37-09-05 |
| ECCN | EAR99 |
| eClass 6 | 27-37-09-05 |
| eClass 7.1 | 27-37-09-05 |
| Packaging Length | 377,00 |
| eClass 8 | 27-37-09-05 |
| Packaging Width | 287,00 |
| Packaging Height | 221,00 |
| REACH | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236 |
| Unit of Measure | ST |
| ETIM 7 | EC001037 |
| Group Classification Key | R711 |
| List of Characteristics | CC-IC10 |
| Metals Coefficient | LA0----- |
| Product ID | 3RK1325-6KS41-2AA0 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 01.07.2006 |
| Configurable Product | False |
| Country of Origin | DE |

Description

SIRIUS motor starter M200D AS-i Communication: AS-Interface DOL starter Standard
Mechanical switching AC-3, 0.75KW / 400 V 0.15 A...2.00 A Electronic overload protection
Thermistor: THERMOCLICK / PTC without brake contact 4 DI / 1 DO AS-i Han Q4/2 - Han Q8/0
with manual on-site operation and key-operated switch