

### 3RK13256LS410AA5

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rk13256ls410aa5
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85371098
Copper Weight	0
EAN	4011209823709.0
eClass 6	27-37-09-05
eClass 7.1	27-37-09-05
eClass 8	27-37-09-05
eClass Version 9	27-37-09-05
eClass Version 9.1	27-37-09-05
Quantity in Package	1
Packaging Length	377,00
Packaging Width	287,00
Packaging Height	221,00
Product Code	3722
Comparative Metals Coefficient	01.07.2006
UPC	662643544220.0
Weight	3661 kg
Product ID	3RK1325-6LS41-0AA5
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.07.2006
Configurable Product	False
Country of Origin	DE
ECCN	EAR99
ETIM 7	EC001037
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Packaging Size	MM
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236
Unit of Measure	ST

## Description

SIRIUS motor starter M200D AS-i Communication: AS-Interface DOL starter Standard  
Mechanical switching AC-3, 5.5 kW / 400 V 1.5 A...12.00 A Electronic overload protection  
Thermistor: THERMOCLICK / PTC with brake contact 180 V DC 4 DI / 1 DO AS-i Han Q4/2 - Han  
Q8/0