

### 3RK14052BG002AA2

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 3rk14052bg002aa2                 |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Legacy / discontinued            |

## Technical specification

|                                |  |
|--------------------------------|--|
| Product ID                     | 3RK1405-2BG00-2AA2   |
| AL Field                       | N  |
| Customs Tariff Code            | 85371098   |
| Compliance                     | Produkt zgodny z RoHS od: 01.05.2012   |
| Configurable Product           | False  |
| Country of Origin              | DE   |
| EAN                            | 4011209974579.0  |
| ECCN                           | N  |
| eClass 6                       | 27-24-26-04  |
| eClass 7.1                     | 27-24-26-04  |
| eClass 8                       | 27-24-26-04  |
| eClass Version 9               | 27-24-26-04  |
| eClass Version 9.1             | 27-24-26-04  |
| ETIM 7                         | EC001599   |
| Group Classification Key       | R711   |
| List of Characteristics        | CC-IC10  |
| Quantity in Package            | 1  |
| Packaging Length               | 159,00   |
| Packaging Width                | 111,00   |
| Packaging Height               | 38,00  |
| Packaging Size                 | MM   |
| Product Description            | Moduł ASIsafe SlimLine Compact SC17.5F digital safety 2F-DI/2DQ, IP20 2 x wejście dla Czujniki mechaniczne 2 x wyjście standardowe DC 24 V Zasilanie wyjścia przełączalne zaciski sprężynowe szerokość 17,5 mm |
| Product Code                   | 3720   |
| Comparative Metals Coefficient | 01.05.2012   |
| REACH                          | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368   |
| Unit of Measure                | ST   |
| UPC                            | 804766359804.0   |
| Weight                         | 183  |

## Description

ASIsafe SlimLine Compact module SC17.5F digital safety 2 F-DI/2 DQ, IP20 2 x input for mechanical sensors 2 x standard output 24 V DC Output supply can be switched spring-type terminals Width 17.5 mm