

### 3RK1902-2HB50

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3rk1902-2hb50
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.15 kgs
<b>Customs Tariff Code</b>	85444290
<b>EAN</b>	4011209854635.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	3722
<b>UPC</b>	662643851366.0
<b>ETIM 7</b>	EC003249
<b>Product ID</b>	3RK1902-2HB50
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.05.2012
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>ECCN</b>	EAR99
<b>eClass 6</b>	27-06-18-01
<b>eClass 7.1</b>	27-06-18-01
<b>eClass 8</b>	27-06-18-01
<b>eClass Version 9</b>	27-06-18-01
<b>eClass Version 9.1</b>	27-06-18-01
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Packaging Length</b>	250,00
<b>Packaging Width</b>	200,00
<b>Packaging Height</b>	50,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	Przewód magistrali do PROFINET jednostronnie konfekcjonowany 4-żyłowy, ekranowany konfekcjonowany z 1 x M12 Kodowanie D długość 5,0 m
<b>Comparative Metals Coefficient</b>	01.05.2012
<b>Unit of Measure</b>	ST